

CARACTERÍSTICAS DE HARDWARE

Estándares y Protocolos	IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS
Interface	1 Fixed Ethernet WAN Port 1 Fixed Ethernet LAN Port 3 Changeable Ethernet WAN/LAN Ports
Medios de Red	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m)
Botón	Reset Button
Fuente de Alimentación	Internal Universal Power Supply AC100-240V~50/60Hz input
Flash	8MB
DRAM	64MB
LED	PWR, SYS, WAN, LAN, WAN/LAN
Dimensiones (W X D X H)	11.6*7.1*1.7in. (294*180*44mm) 13-inch Standard Rack-Mount Width, 1U Height
RENDIMIENTO	
Sesiones Concurrentes	30000
FUNCIONES BÁSICAS	
WAN Connection Type	Static/Dynamic IP, PPPoE, PPTP, L2TP, Dual Access, Bigpond Cable
MAC Clone	Modify WAN/LAN MAC Address
DHCP	DHCP Server/Client, DHCP Address Reservation
Configuración Switch	Port Mirror, Rate Control, Port Configuration, Port VLAN
FUNCIONES AVANZADAS	
ACL	IP/MAC/URL/WEB Filtering
IGMP	IGMP Proxy/IGMP Snooping
Forwarding	Virtual Server, Port Triggering, DMZ
Equilibrio de carga	Policy Routing, Link Backup
NAT	One-to-One NAT, Multi-Nets NAT
Routing	Static Routing
Seguridad	FTP/SIP/PPTP/IPsec/H.323 ALG, DoS Defence, Ping of Death
Control de Trafico	Bandwidth Control, Session Limit
ADMINISTRACIÓN	
Servicio	PPPoE Server, E-Bulletin, Dynamic DNS, UPnP, App Control
Mantenimiento	Time Setting, Daylight Saving Time, SNMP, Diagnostics, Firmware Upgrade, Factory Defaults/Reboot, Backup/Restore, System Log, Remote Management, Statistics
OTROS	
Certificacion	CE, FCC, RoHS
Contenido del paquete	TL-R480T+ Power Cord RJ-45 Ethernet Cable Installation Guide Resource CD
Requisitos del Sistema	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing