

## CARACTERÍSTICAS DE HARDWARE

Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Botón	WPS/RESET Button
Fuente de Alimentación Externa	9VDC / 0.6A
Estándares Inalámbricos	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensiones (W X D X H)	7.2 x 5.0 x 1.4in.(182 x 128 x 35 mm)
Antenas	2 Antennas

## CARACTERÍSTICAS INALÁMBRICAS

Frecuencia	2.4-2.4835GHz
Tasa de Señal	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Potencia de Transmision	CE: <20dBm FCC: <30dBm
Funciones Inalámbricas	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Seguridad Inalámbrica	64/128-bit WEP, WPA / WPA2,WPA-PSK / WPA2-PSK

## CARACTERÍSTICAS DE SOFTWARE

Calidad de servicio	WMM, Bandwidth Control
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP
Administración	Access Control Local Management Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Control de Acceso	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Seguridad de cortafuegos	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocolos	Support IPv4 and IPv6
Red de invitados	2.4GHz Guest Network x1

## OTROS

Certificacion	CE, RoHS
Contenido del paquete	Wireless N Router TL-WR850N Power supply unit Ethernet Cable Quick Installation Guide
Requisitos del Sistema	Windows 2000/XP/Vista™, Windows 7, Windows 8, Windows 8.1, Windows 10 or Mac OS or Linux-based operating system
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing