

# MC111CS

## CONVERTIDOR DE MEDIOS Y MÓDULO

Standards and Protocols	IEEE 802.3i, IEEE 802.3u
Basic Function	Adopts WDM technology Half/Full-Duplex transfer mode for FX port Extends fiber distance up to 20km
Ports	1 100M SC/UPC port 1 10/100M RJ45 port (Auto MDI/MDIX)
Wave Length	1550nm Tx/1310nm Rx
WDM TX	1550nm
WDM RX	1310nm
Network Media 10BASE-T	UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media 100BASE-T	UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media 100BASE-FX	Single-mode Fiber
LED Indicators	PWR, Link/Act
Dimensions (W*D*H)	3.7*2.9*1.1 in. (94.5*73.0*27.0 mm)
Power Supply	External Power Adapter
Max Power Consumption	1.23W
Safety & Emission	FCC, CE, RoHS
Package Contents	<ul style="list-style-type: none"><li>• Media Converter MC111CS</li><li>• Power Adapter</li><li>• Installation Guide</li></ul>
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing